



FIRE & SAFETY

EQUIPMENT COMPANY



STORM SURGE



WWW.FIREANDSAFETY.COM



WHY BUY TNT?

1

100% MANUFACTURED IN THE USA.

It's easy to stick an American flag on a tool to be patriotic but TNT's flag isn't just an ornament. Manufacturing 100% in the USA!

2

THE ONLY FOREVER WARRANTY.

Others claim to have a "Lifetime Warranty", which they pro-rate. There are never questions on what is/isn't covered. TNT's warranty means what it says, FOREVER.

3

EASIER TO MAINTAIN / LOWEST COST OF OWNERSHIP.

TNT's battery-operated rescue tools only require an oil change after ten years of service.

4

MILWAUKEE, DEWALT, OR MAKITA BATTERIES.

The only tool in the world to offer 3 choices of batteries. TNT uses non-proprietary batteries. Benefits are PRICE & AVAILABILITY. TNT's battery costs are never hidden.

5

USES A BRUSHED DC MOTOR MAKING IT THE MOST EFFICIENT BATTERY-OPERATED TOOL.

Increases battery operating time, and allows for a smaller circuit board, thus running cooler and outperforming any competitor.

6

TNT IS A FAMILY-OWNED AND OPERATED BUSINESS.

No corporate red tape involved which means any promises above are kept!



LOCALLY OWNED
AND OPERATED





**2 BATTERIES
AND
1 CHARGER**



FREE!
WITH EVERY TOOL!



LOCALLY OWNED
AND OPERATED





I N D E X

WELCOME	PG 1
FOREVER WARRANTY	PG 2
CUTTERS	PG 3-4
COMBI NATION CUTTER / SPREADER	PG 5
SPREADERS	PG 6-8
RAMS	PG 9-10
ACCESSORIES	PG 11-12
ISO	PG 13





Welcome to TNT Rescue Systems, Inc, the premier manufacturer of Powered Hydraulic Rescue Tools. The employees and distributors are delighted with your interest in our products and look forward to a long and mutually beneficial relationship.

Blanton & Company began as an OEM manufacturer of Industrial hydraulic pumps. Entry into the rescue tool world came by way of one of our early customers, with the **Blanton design of the first true 2 tool simultaneous operation pump**. Owner and President Tom Blanton, noted a lack of customer service in the rescue tool market, creating the initial vision of what would become TNT Rescue Systems, Inc.

TNT Rescue Systems Inc's vision is simple: design, build, and distribute the highest quality hydraulic rescue tools, **provide a Forever Warranty** and support the customer with the highest level of service. The dedication to service is shown everyday by the family of TNT Rescue Systems, Inc. From employees at the factory, management, or our dealers we have current and retired firefighters throughout our organization and fully understand the expectations of tool performance on the street.

TNT Rescue Systems, Inc. understands the service you need from you rescue tools and your tool manufacturer. **Dedication to our customers continues with our Forever Warranty. Our warranty is the most comprehensive in the industry, providing coverage for our products.** Whether you're a dealer or end user we are committed to providing you with exceptional customer service. Our customer-focused method of doing business has been the standard at TNT Rescue Systems Inc, (Blanton & Company) since its start in 1986.

TNT Rescue Systems, Inc. is 100% owned and operated with our only facility solely located in Ashippun, Wisconsin.

To that end, TNT Rescue Systems, Inc. is a ISO 9001:2015 registered company and builds tools to exceed the minimum performance standard of NFPA 1936 & EN 13204





TNT RESCUE SYSTEMS STORM-SURGE SERIES BATTERY-OPERATED EXTRICATION TOOLS ARE **POWERED BY THE MILWAUKEE M18, DEWALT® 20V, OR MAKITA 18V PLATFORMS, MAKING THEM THE LONGEST-RUNNING PORTABLE RESCUE TOOLS ON THE MARKET. THE END-USER BENEFITS FROM THE PRICE AND AVAILABILITY USING THESE OEM NON-PROPRIETARY BATTERIES.**

THE TOOLS FEATURE AN ALL-NEW WELL BALANCED COMPACT ALUMINIUM DESIGN, WITH **TOOL SPEEDS THAT ARE UNMATCHED UNDER BOTH LOADED AND UNLOADED CONDITIONS WITH NO DEGRADATION IN POWER.** WITH THIS NEW DESIGN, IT MAKES IT POSSIBLE TO DO RELIEF CUTS IN TIGHT POSITIONS WHERE OTHER MANUFACTURERS CANT. THE BATTERY TERMINAL IS LOCATED ON THE TOP OF THE TOOL BETWEEN THE CARRY HANDLE AND CONTROL VALVE, PROVIDING BETTER PROTECTION AND SAFETY.

CONTACT FIRE & SAFETY EQUIPMENT COMPANY FOR MORE INFORMATION OR THEIR WEBSITE.

WWW.FIREANDSAFETY.COM/OUR-BRANDS/TNT-RESCUE



2



FIRE & SAFETY

EQUIPMENT COMPANY



ESLC-29-18V

LENGTH 32.99 IN
HEIGHT 11.69 IN
WIDTH 10.5 IN
WEIGHT
EXCL. BATTERY 51.40 LBS
INCL. BATTERY 53.75 LBS
MAX. BLADE OPENING 8.00 IN
MAX. CUT REACH 5.08 IN
POWER SOURCE OPTION MILWAUKEE M18
CERTIFIED TO NFPA 1936-2020 YES
NFPA CUT TEST A8, B9, C9, D9, E9, F5
IP RATING 54



ESLC-29-20V

LENGTH 32.99 IN
HEIGHT 11.69 IN
WIDTH 10.50 IN
WEIGHT
EXCL. BATTERY 51.40 LBS
INCL. BATTERY 54.60 LBS
MAX. BLADE OPENING 8.00 IN
MAX. CUT REACH 5.08 IN
POWER SOURCE OPTION DEWALT 20V
CERTIFIED TO NFPA 1936-2020 YES
NFPA CUT TEST A8, B9, C9, D9, E9, F5
IP RATING 54



FIRE & SAFETY

EQUIPMENT COMPANY



EBFC-320-18V

LENGTH 35.81 IN
HEIGHT 11.81 IN
WIDTH 10.50 IN
WEIGHT
EXCL. BATTERY 61.55 LBS
INCL. BATTERY 63.90 LBS
MAX. BLADE OPENING 8.6 IN
MAX. CUT REACH 4.75 IN
POWER SOURCE OPTION MILWAUKEE M18
CERTIFIED TO NFPA 1936-2020 YES
NFPA CUT TEST A9, B9, C9, D9, E9, F6
IP RATING 54



EBFC-320-20V

LENGTH 35.81 IN
HEIGHT 11.81 IN
WIDTH 10.50 IN
WEIGHT
EXCL. BATTERY 61.55 LBS
INCL. BATTERY 64.75 LBS
MAX. BLADE OPENING 8.6 IN
MAX. CUT REACH 4.75 IN
POWER SOURCE OPTION DEWALT 20V
CERTIFIED TO NFPA 1936-2020 YES
NFPA CUT TEST A9, B9, C9, D9, E9, F6
IP RATING 54



STORM SURGE

4



BUILT TO RESCUE



EBFCC-28-18V

LENGTH 36.21 IN
HEIGHT 11.74 IN
WIDTH 10.50 IN
WEIGHT
EXCL. BATTERY 52.75 LBS
INCL. BATTERY 55.08 LBS
MAX. BLADE OPENING 10.12 IN
MAX. CUT REACH 5.55 IN
MAX. SPREAD DISTANCE 17.00 IN
MAX. SPREAD FORCE 286,000 LBF
POWER SOURCE OPTION MILWAUKEE M18
CERTIFIED TO NFPA 1936-2020 YES
NFPA CUT TEST A8, B7, C8, D8, E9, F5
IP RATING 54



EBFCC-28-20V

LENGTH 36.21 IN
HEIGHT 11.74 IN
WIDTH 10.50 IN
WEIGHT
EXCL. BATTERY 52.75 LBS
INCL. BATTERY 55.95 LBS
MAX. BLADE OPENING 10.12 IN
MAX. CUT REACH 5.55 IN
MAX. SPREAD DISTANCE 17.00 IN
MAX. SPREAD FORCE 286,000 LBF
POWER SOURCE OPTION DEWALT 20V
CERTIFIED TO NFPA 1936-2020 YES
NFPA CUT TEST A8, B7, C8, D8, E9, F5
IP RATING 54





ES100-24-18V

LENGTH 32.43 IN
HEIGHT 11.15 IN
WIDTH 13.58 IN
WEIGHT
EXCL. BATTERY 46.85 LBS
INCL. BATTERY 49.20 LBS
MAX. SPREAD DISTANCE 23.50 IN
MAX. SPREAD FORCE RANGE 64,476 - 242,368 LBF
MAX. PULL DISTANCE 14.25 IN
MAX. PULL FORCE 14,368 LBF
POWER SOURCE OPTION MILWAUKEE M18
CERTIFIED TO NFPA 1936-2020 YES
IP RATING 54



ES100-24-20V

LENGTH 32.43 IN
HEIGHT 11.15 IN
WIDTH 13.58 IN
WEIGHT
EXCL. BATTERY 46.85 LBS
INCL. BATTERY 50.05 LBS
MAX. SPREAD DISTANCE 23.50 IN
MAX. SPREAD FORCE RANGE 64,476 - 242,368 LBF
MAX. PULL DISTANCE 14.25 IN
MAX. PULL FORCE 14,368 LBF
POWER SOURCE OPTION DEWALT 20V **CERTIFIED**
TO NFPA 1936-2020 YES
IP RATING 54



ES100-28-18V



LENGTH 34.80 IN
HEIGHT 11.15 IN
WIDTH 13.58 IN
WEIGHT
EXCL. BATTERY 48.20 LBS
INCL. BATTERY 50.55 LBS
MAX. SPREAD DISTANCE 27.50 IN
MAX. SPREAD FORCE RANGE 56,128 - 228,126 LBF
MAX. PULL DISTANCE 18.25 IN
MAX. PULL FORCE 11,168 LBF
POWER SOURCE OPTION MILWAUKEE M18
CERTIFIED TO NFPA 1936-2020 YES
IP RATING 54



ES100-28-20V

LENGTH 34.80 IN
HEIGHT 11.15 IN
WIDTH 13.58 IN
WEIGHT
EXCL. BATTERY 48.20 LBS
INCL. BATTERY 51.40 LBS
MAX. SPREAD DISTANCE 27.50 IN
MAX. SPREAD FORCE RANGE 56,128 - 228,126 LBF
MAX. PULL DISTANCE 18.25 IN
MAX. PULL FORCE 11,168 LBF
POWER SOURCE OPTION DEWALT 20V
CERTIFIED TO NFPA 1936-2020 YES
IP RATING 54





ES100-32-18V

LENGTH 37.17 IN
HEIGHT 11.15 IN
WIDTH 13.58 IN
WEIGHT
EXCL. BATTERY 49.45 LBS
INCL. BATTERY 51.80 LBS
MAX. SPREAD DISTANCE 31,50 IN
MAX. SPREAD FORCE RANGE 50,592 - 201,420 LBF
MAX. PULL DISTANCE 22.25 IN
MAX. PULL FORCE 9,339 LBF
POWER SOURCE OPTION MILWAUKEE M18
CERTIFIED TO NFPA 1936-2020 YES
IP RATING 54



ES100-32-20V

LENGTH 37.17 IN
HEIGHT 11.15 IN
WIDTH 13.58 IN
WEIGHT
EXCL. BATTERY 49.45 LBS
INCL. BATTERY 52.65 LBS
MAX. SPREAD DISTANCE 31,50 IN
MAX. SPREAD FORCE RANGE 50,592 - 201,420 LBF
MAX. PULL DISTANCE 22.25 IN
MAX. PULL FORCE 9,339 LBF
POWER SOURCE OPTION DEWALT 20V
CERTIFIED TO NFPA 1936-2020 YES
IP RATING 54





ER-40-18V

CLOSED LENGTH 25.50 IN
EXTENDED LENGTH 41.00 IN
HEIGHT 10.75 IN
WIDTH 8.10 IN
WEIGHT
EXCL. BATTERY 41.25 LBS
INCL. BATTERY 43.60 LBS
MAX. PUSH FORCE 37,005 LBF
MAX. PULL FORCE 8,293 LBF
POWER SOURCE OPTION MILWAUKEE M18
CERTIFIED TO NFPA 1936-2020 YES
IP RATING 54



ER-40-20V

CLOSED LENGTH 25.50 IN
EXTENDED LENGTH 41.00 IN
HEIGHT 10.75 IN
WIDTH 8.10 IN
WEIGHT
EXCL. BATTERY 41.25 LBS
INCL. BATTERY 44.45 LBS
MAX. PUSH FORCE 37,005 LBF
MAX. PULL FORCE 8,293 LBF
POWER SOURCE OPTION DEWALT 20V
CERTIFIED TO NFPA 1936-2020 YES
IP RATING 54



STORM SURGE





ETLS-40-18V

CLOSED LENGTH 21.50 IN
EXTENDED LENGTH 42.25 IN
HEIGHT 10.75 IN
WIDTH 8.10 IN
WEIGHT
EXCL. BATTERY 38.75 LBS
INCL. BATTERY 41.10 LBS
1ST STAGE STROKE 12.95 IN
1ST STAGE MAX. PUSH FORCE 38.067 LBF
2ND STAGE STROKE 8.70 IN
2ND STAGE MAX. PUSH FORCE 13.088 LBF
POWER SOURCE OPTION MILWAUKEE M18
CERTIFIED TO NFPA 1936-2020 YES
IP RATING 54



ETLS-40-20V

CLOSED LENGTH 21.50 IN
EXTENDED LENGTH 42.25 IN
HEIGHT 10.75 IN
WIDTH 8.10 IN
WEIGHT
EXCL. BATTERY 38.75 LBS
INCL. BATTERY 41.95 LBS
1ST STAGE STROKE 12.95 IN
1ST STAGE MAX. PUSH FORCE 38.067 LBF
2ND STAGE STROKE 8.70 IN
2ND STAGE MAX. PUSH FORCE 13.088 LBF
POWER SOURCE OPTION DEWALT 20V
CERTIFIED TO NFPA 1936-2020 YES
IP RATING 54



10





STORM SURGE

RAM BASE EXTENSION-KIT

6 INCH RAM BASE EXTENSION

ASSEMBLED LENGTH 10.35 IN

MAXIMUM EXTENDED LENGTH

ER-40 WITH EXTENSION 48.75 IN

ETLS-40 WITH EXTENSION 50.00 IN

12 INCH RAM BASE EXTENSION

ASSEMBLED LENGTH 16.35 IN

MAXIMUM EXTENDED LENGTH

ER-40 WITH EXTENSION 54.75 IN

ETLS-40 WITH EXTENSION 56.00 IN

18 INCH RAM BASE EXTENSION

ASSEMBLED LENGTH 22.35 IN

MAXIMUM EXTENDED LENGTH

ER-40 WITH EXTENSION 60.75 IN

ETLS-40 WITH EXTENSION 62.00 IN





R-KIT



XR-KIT



570220-M18-8AH



570221-M18 DUAL
RAPID CHARGER



570222-20V/60V-9AH



570223-DCB118 SINGLE
FAST CHARGER



570225-18V - 6AH



570226-DC18RD DUAL
RAPID CHARGER





ISO 9001-2015

The International for Standardization (ISO) is a network of national standards instituted in 157 countries. Each ISO member is the leading standards organization in its country. These members devise new standards, work to advance them, and team up with the ISO Central Secretariat to guide the technical groups that develop them.

They award certification only after registered, independent auditors review a company's process against strict ISO standards, and verify that the company has met established requirements, in both policy and practice.

TNT Rescue Systems Inc. is certified as an ISO 9001:2015 registered firm. This means you can be sure that TNT Rescue Systems Inc. products are designed and manufactured to the high standards our industry - and the ISO - demands. Certification covers all that we do to enhance customer satisfaction by meeting both customer and regulatory requirements, while continually improving performance.



PERFORMANCE,
QUALITY
AND SERVICE
GUARANTEED!





FIRE & SAFETY
EQUIPMENT COMPANY

FOR MORE DETAILED INFORMATION OR TO
SCHEDULE A DEMO PLEASE REACH OUT:

WWW.FIREANDSAFETY.COM



TNT@FIREANDSAFETY.COM

