



# FIRE & SAFETY

EQUIPMENT COMPANY



## STORM SURGE



[WWW.FIREANDSAFETY.COM](http://WWW.FIREANDSAFETY.COM)





**TNT RESCUE**  
BUILT TO RESCUE



## WHY BUY TNT?

1

### **100% MANUFACTURED IN THE USA.**

TNT's flag isn't just an ornament. Manufacturing 100% in the USA!

2

### **THE ONLY "FOREVER WARRANTY".**

Others claim to have a "Lifetime Warranty", which they pro-rate. There are never questions on what is/isn't covered. Parts & labor covered FOREVER!

3

### **EASIER TO MAINTAIN / LOWEST COST OF OWNERSHIP.**

TNT's battery-operated rescue tools only require an oil change after ten years of service.

4

### **MILWAUKEE, DEWALT, OR MAKITA BATTERIES.**

The only tool in the world to offer 3 choices of batteries. TNT uses non-proprietary batteries. Benefits are PRICE & AVAILABILITY. TNT's battery costs are never hidden.

5

### **USES A DC MOTOR MAKING IT THE MOST EFFICIENT.**

Increases battery operating time, and allows for a smaller circuit board, thus running cooler and outperforming any competitors which require a DC/AC inverter.

6

### **TNT IS A FAMILY-OWNED AND OPERATED BUSINESS.**

No corporate red tape involved which means any promises above are kept!







**TNT RESCUE**  
BUILT TO RESCUE



**2 BATTERIES  
AND  
CHARGER**



**FREE!**



**\*\*Choose between  
Milwaukee, Dewalt, or  
Makita.\*\***

**WITH EVERY TOOL!**



**LOCALLY OWNED  
AND OPERATED**

**FIRE & SAFETY**  
EQUIPMENT COMPANY





## INDEX

WELCOME	PG 1
FOREVER WARRANTY	PG 2
CUTTERS	PG 3-4
COMBI-CUTTER/SPREADER	PG 5
SPREADERS	PG 6-8
RAMS	PG 9-10
ACCESSORIES	PG 11-12
NEW CUTTER & COMBI (2024)	PG 13-14
ISO	PG 15
MILWAUKEE ONE-KEY	PG 16-17







Welcome to TNT Rescue Systems, Inc, the premier manufacturer of Powered Hydraulic Rescue Tools. The employees and distributors are delighted with your interest in our products and look forward to a long and mutually beneficial relationship.

Blanton & Company began as an OEM manufacturer of Industrial hydraulic pumps. Entry into the rescue tool world came by way of one of our early customers, with the **Blanton design of the first true 2 tool simultaneous operation pump**. Owner and President Tom Blanton, noted a lack of customer service in the rescue tool market, creating the initial vision of what would become TNT Rescue Systems, Inc.

TNT Rescue Systems Inc's vision is simple: design, build, and distribute the highest quality hydraulic rescue tools, **provide a Forever Warranty** and support the customer with the highest level of service. The dedication to service is shown everyday by the family of TNT Rescue Systems, Inc. From employees at the factory, management, or our dealers we have current and retired firefighters throughout our organization and fully understand the expectations of tool performance on the street.

TNT Rescue Systems, Inc. understands the service you need from you rescue tools and your tool manufacturer. **Dedication to our customers continues with our Forever Warranty. Our warranty is the most comprehensive in the industry, providing coverage for our products.** Whether you're a dealer or end user we are committed to providing you with exceptional customer service. Our customer-focused method of doing business has been the standard at TNT Rescue Systems Inc, ( Blanton & Company ) since its start in 1986.

TNT Rescue Systems, Inc. is 100% owned and operated with our only facility solely located in Ashippun, Wisconsin.

To that end, TNT Rescue Systems, Inc. is a ISO 9001:2015 registered company and builds tools to exceed the minimum performance standard of NFPA 1936 & EN 13204







TNT RESCUE SYSTEMS STORM-SURGE SERIES BATTERY-OPERATED EXTRICATION TOOLS ARE **POWERED BY THE MILWAUKEE M18, DEWALT® 20V, OR MAKITA 18V PLATFORMS, MAKING THEM THE LONGEST-RUNNING PORTABLE RESCUE TOOLS ON THE MARKET. THE END-USER BENEFITS FROM THE PRICE AND AVAILABILITY USING THESE OEM NON-PROPRIETARY BATTERIES.**

THE TOOLS FEATURE AN ALL-NEW WELL BALANCED COMPACT ALUMINIUM DESIGN, WITH **TOOL SPEEDS THAT ARE UNMATCHED UNDER BOTH LOADED AND UNLOADED CONDITIONS WITH NO DEGRADATION IN POWER.** WITH THIS NEW DESIGN, IT MAKES IT POSSIBLE TO DO RELIEF CUTS IN TIGHT POSITIONS WHERE OTHER MANUFACTURERS CANT. THE BATTERY TERMINAL IS LOCATED ON THE TOP OF THE TOOL BETWEEN THE CARRY HANDLE AND CONTROL VALVE, PROVIDING BETTER PROTECTION AND SAFETY.

CONTACT FIRE & SAFETY EQUIPMENT COMPANY FOR MORE INFORMATION OR THEIR WEBSITE.

[WWW.FIREANDSAFETY.COM/OUR-BRANDS/TNT-RESCUE](http://WWW.FIREANDSAFETY.COM/OUR-BRANDS/TNT-RESCUE)



2





# FIRE & SAFETY

EQUIPMENT COMPANY



## ESLC-29-18V

LENGTH 32.99 IN  
HEIGHT 11.69 IN  
WIDTH 10.5 IN  
WEIGHT  
EXCL. BATTERY 51.40 LBS  
INCL. BATTERY 53.75 LBS  
MAX. BLADE OPENING 8.00 IN  
MAX. CUT REACH 5.08 IN  
POWER SOURCE OPTION MILWAUKEE M18  
CERTIFIED TO NFPA 1936-2020 YES  
NFPA CUT TEST A8, B9, C9, D9, E9, F5  
IP RATING 54



## ESLC-29-20V

LENGTH 32.99 IN  
HEIGHT 11.69 IN  
WIDTH 10.50 IN  
WEIGHT  
EXCL. BATTERY 51.40 LBS  
INCL. BATTERY 54.60 LBS  
MAX. BLADE OPENING 8.00 IN  
MAX. CUT REACH 5.08 IN  
POWER SOURCE OPTION DEWALT 20V  
CERTIFIED TO NFPA 1936-2020 YES  
NFPA CUT TEST A8, B9, C9, D9, E9, F5  
IP RATING 54



# STORM SURGE



# FIRE & SAFETY

EQUIPMENT COMPANY



## ESLC-29-18V

LENGTH 32.99 IN  
HEIGHT 11.69 IN  
WIDTH 10.5 IN  
WEIGHT  
EXCL. BATTERY 51.40 LBS  
INCL. BATTERY 53.75 LBS  
MAX. BLADE OPENING 8.00 IN  
MAX. CUT REACH 5.08 IN  
POWER SOURCE OPTION MILWAUKEE M18  
CERTIFIED TO NFPA 1936-2020 YES  
NFPA CUT TEST A8, B9, C9, D9, E9, F5  
IP RATING 54



## ESLC-29-20V

LENGTH 32.99 IN  
HEIGHT 11.69 IN  
WIDTH 10.50 IN  
WEIGHT  
EXCL. BATTERY 51.40 LBS  
INCL. BATTERY 54.60 LBS  
MAX. BLADE OPENING 8.00 IN  
MAX. CUT REACH 5.08 IN  
POWER SOURCE OPTION DEWALT 20V  
CERTIFIED TO NFPA 1936-2020 YES  
NFPA CUT TEST A8, B9, C9, D9, E9, F5  
IP RATING 54



4







**EBFCC-28-18V**

LENGTH 36.21 IN  
 HEIGHT 11.74 IN  
 WIDTH 10.50 IN  
 WEIGHT  
 EXCL. BATTERY 52.75 LBS  
 INCL. BATTERY 55.08 LBS  
 MAX. BLADE OPENING 10.12 IN  
 MAX. CUT REACH 5.55 IN  
 MAX. SPREAD DISTANCE 17.00 IN  
 MAX. SPREAD FORCE 286,000 LBF  
 POWER SOURCE OPTION MILWAUKEE M18  
 CERTIFIED TO NFPA 1936-2020 YES  
 NFPA CUT TEST A8, B7, C8, D8, E9, F5  
 IP RATING 54



**EBFCC-28-20V**

LENGTH 36.21 IN  
 HEIGHT 11.74 IN  
 WIDTH 10.50 IN  
 WEIGHT  
 EXCL. BATTERY 52.75 LBS  
 INCL. BATTERY 55.95 LBS  
 MAX. BLADE OPENING 10.12 IN  
 MAX. CUT REACH 5.55 IN  
 MAX. SPREAD DISTANCE 17.00 IN  
 MAX. SPREAD FORCE 286,000 LBF  
 POWER SOURCE OPTION DEWALT 20V  
 CERTIFIED TO NFPA 1936-2020 YES  
 NFPA CUT TEST A8, B7, C8, D8, E9, F5  
 IP RATING 54



**STORM SURGE**





**ES100-24-18V**

**LENGTH** 32.43 IN  
**HEIGHT** 11.15 IN  
**WIDTH** 13.58 IN  
**WEIGHT**  
**EXCL. BATTERY** 46.85 LBS  
**INCL. BATTERY** 49.20 LBS  
**MAX. SPREAD DISTANCE** 23.50 IN  
**MAX. SPREAD FORCE RANGE** 64,476 - 242,368 LBF  
**MAX. PULL DISTANCE** 14.25 IN  
**MAX. PULL FORCE** 14,368 LBF  
**POWER SOURCE OPTION** MILWAUKEE M18  
**CERTIFIED TO NFPA 1936-2020** YES  
**IP RATING** 54



**ES100-24-20V**

**LENGTH** 32.43 IN  
**HEIGHT** 11.15 IN  
**WIDTH** 13.58 IN  
**WEIGHT**  
**EXCL. BATTERY** 46.85 LBS  
**INCL. BATTERY** 50.05 LBS  
**MAX. SPREAD DISTANCE** 23.50 IN  
**MAX. SPREAD FORCE RANGE** 64,476 - 242,368 LBF  
**MAX. PULL DISTANCE** 14.25 IN  
**MAX. PULL FORCE** 14,368 LBF  
**POWER SOURCE OPTION** DEWALT 20V **CERTIFIED**  
**TO NFPA 1936-2020** YES  
**IP RATING** 54





**ES100-28-18V**



LENGTH 34.80 IN  
 HEIGHT 11.15 IN  
 WIDTH 13.58 IN  
 WEIGHT  
 EXCL. BATTERY 48.20 LBS  
 INCL. BATTERY 50.55 LBS  
 MAX. SPREAD DISTANCE 27.50 IN  
 MAX. SPREAD FORCE RANGE 56,128 - 228,126 LBF  
 MAX. PULL DISTANCE 18.25 IN  
 MAX. PULL FORCE 11,168 LBF  
 POWER SOURCE OPTION MILWAUKEE M18  
 CERTIFIED TO NFPA 1936-2020 YES  
 IP RATING 54



**ES100-28-20V**

LENGTH 34.80 IN  
 HEIGHT 11.15 IN  
 WIDTH 13.58 IN  
 WEIGHT  
 EXCL. BATTERY 48.20 LBS  
 INCL. BATTERY 51.40 LBS  
 MAX. SPREAD DISTANCE 27.50 IN  
 MAX. SPREAD FORCE RANGE 56,128 - 228,126 LBF  
 MAX. PULL DISTANCE 18.25 IN  
 MAX. PULL FORCE 11,168 LBF  
 POWER SOURCE OPTION DEWALT 20V  
 CERTIFIED TO NFPA 1936-2020 YES  
 IP RATING 54





**ES100-32-18V**

LENGTH 37.17 IN  
HEIGHT 11.15 IN  
WIDTH 13.58 IN  
WEIGHT  
EXCL. BATTERY 49.45 LBS  
INCL. BATTERY 51.80 LBS  
MAX. SPREAD DISTANCE 31,50 IN  
MAX. SPREAD FORCE RANGE 50,592 - 201,420 LBF  
MAX. PULL DISTANCE 22.25 IN  
MAX. PULL FORCE 9,339 LBF  
POWER SOURCE OPTION MILWAUKEE M18  
CERTIFIED TO NFPA 1936-2020 YES  
IP RATING 54



**ES100-32-20V**

LENGTH 37.17 IN  
HEIGHT 11.15 IN  
WIDTH 13.58 IN  
WEIGHT  
EXCL. BATTERY 49.45 LBS  
INCL. BATTERY 52.65 LBS  
MAX. SPREAD DISTANCE 31,50 IN  
MAX. SPREAD FORCE RANGE 50,592 - 201,420 LBF  
MAX. PULL DISTANCE 22.25 IN  
MAX. PULL FORCE 9,339 LBF  
POWER SOURCE OPTION DEWALT 20V  
CERTIFIED TO NFPA 1936-2020 YES  
IP RATING 54







**ER-40-18V**

**CLOSED LENGTH** 25.50 IN  
**EXTENDED LENGTH** 41.00 IN  
**HEIGHT** 10.75 IN  
**WIDTH** 8.10 IN  
**WEIGHT**  
**EXCL. BATTERY** 41.25 LBS  
**INCL. BATTERY** 43.60 LBS  
**MAX. PUSH FORCE** 37,005 LBF  
**MAX. PULL FORCE** 8,293 LBF  
**POWER SOURCE OPTION** MILWAUKEE M18  
**CERTIFIED TO NFPA 1936-2020** YES  
**IP RATING** 54



**ER-40-20V**

**CLOSED LENGTH** 25.50 IN  
**EXTENDED LENGTH** 41.00 IN  
**HEIGHT** 10.75 IN  
**WIDTH** 8.10 IN  
**WEIGHT**  
**EXCL. BATTERY** 41.25 LBS  
**INCL. BATTERY** 44.45 LBS  
**MAX. PUSH FORCE** 37,005 LBF  
**MAX. PULL FORCE** 8,293 LBF  
**POWER SOURCE OPTION** DEWALT 20V  
**CERTIFIED TO NFPA 1936-2020** YES  
**IP RATING** 54





**ETLS-40-18V**

**CLOSED LENGTH** 21.50 IN  
**EXTENDED LENGTH** 42.25 IN  
**HEIGHT** 10.75 IN  
**WIDTH** 8.10 IN  
**WEIGHT**  
**EXCL. BATTERY** 38.75 LBS  
**INCL. BATTERY** 41.10 LBS  
**1ST STAGE STROKE** 12.95 IN  
**1ST STAGE MAX. PUSH FORCE** 38.067 LBF  
**2ND STAGE STROKE** 8.70 IN  
**2ND STAGE MAX. PUSH FORCE** 13.088 LBF  
**POWER SOURCE OPTION** MILWAUKEE M18  
**CERTIFIED TO NFPA 1936-2020** YES  
**IP RATING** 54



**ETLS-40-20V**

**CLOSED LENGTH** 21.50 IN  
**EXTENDED LENGTH** 42.25 IN  
**HEIGHT** 10.75 IN  
**WIDTH** 8.10 IN  
**WEIGHT**  
**EXCL. BATTERY** 38.75 LBS  
**INCL. BATTERY** 41.95 LBS  
**1ST STAGE STROKE** 12.95 IN  
**1ST STAGE MAX. PUSH FORCE** 38.067 LBF  
**2ND STAGE STROKE** 8.70 IN  
**2ND STAGE MAX. PUSH FORCE** 13.088 LBF  
**POWER SOURCE OPTION** DEWALT 20V  
**CERTIFIED TO NFPA 1936-2020** YES  
**IP RATING** 54



**10**







**STORM SURGE**

**RAM BASE EXTENSION-KIT**

**6 INCH RAM BASE EXTENSION**

ASSEMBLED LENGTH 10.35 IN

MAXIMUM EXTENDED LENGTH

ER-40 WITH EXTENSION 48.75 IN

ETLS-40 WITH EXTENSION 50.00 IN

**12 INCH RAM BASE EXTENSION**

ASSEMBLED LENGTH 16.35 IN

MAXIMUM EXTENDED LENGTH

ER-40 WITH EXTENSION 54.75 IN

ETLS-40 WITH EXTENSION 56.00 IN

**18 INCH RAM BASE EXTENSION**

ASSEMBLED LENGTH 22.35 IN

MAXIMUM EXTENDED LENGTH

ER-40 WITH EXTENSION 60.75 IN

ETLS-40 WITH EXTENSION 62.00 IN





**FIRE & SAFETY**  
EQUIPMENT COMPANY



**R-KIT**



**XR-KIT**



570220-M18-8AH



570221-M18 DUAL  
RAPID CHARGER



570222-20V/60V-9AH



570223-DCB118 SINGLE  
FAST CHARGER



570225-18V - 6AH



570226-DC18RD DUAL  
RAPID CHARGER



12







# ESLC-30



**LENGTH** 31.5 IN 800.10 MM

**HEIGHT** 11.74 IN 298.13 MM

**WIDTH** 10.50 IN 266.70 MM

**WEIGHT**

**EXCL. BATTERY** 50.6 LBS 22.95 KG

**BATTERY WEIGHT:**

MILWAUKEE M18-9AH: 2.4 LBS 1.08 KG

DEWALT 20/60V-9AH: 3.4 LBS 1.54 KG

MAKITA 18V LXT-6AH 1.5 LBS 0.68 KG

**MAX. BLADE OPENING** 8.25 IN 215.9 MM

**MAX. CUT REACH** 5.37 IN 136.52 MM

**MAX. CUT FORCE** 300,000 LBF 1,334 KN

**NFPA CUT RATING** A8/B9/C9/D9/E9/F5

**POWER SOURCE OPTION**

MILWAUKEE M18, MAKITA LXT 18V AND DEWALT 20V

**IP RATING** 54

BUILT TO  
RESCUE





# ESLCC-24



**LENGTH** 29.5 IN 749 MM

**HEIGHT** 11.74 IN 298.13 MM

**WIDTH** 10.50 IN 266.70 MM

**WEIGHT**

**EXCL. BATTERY** 39.8 LBS 18.05 KG

**BATTERY WEIGHT:**

MILWAUKEE M18-9AH: 2.4 LBS 1.08 KG

DEWALT 20/60V-9AH: 3.4 LBS 1.54 KG

MAKITA 18V LXT-6AH 1.5 LBS 0.68 KG

**MAX. BLADE OPENING** 9.5 IN 241.3 MM

**MAX. CUT REACH** 3.75 IN 95.25 MM

**MAX. SPREAD DISTANCE** 12 IN 304.8 MM

**MAX. SPREAD FORCE** 240,00 LBF 1,067 KN

**POWER SOURCE OPTION**

MILWAUKEE M18, MAKITA LXT 18V AND DEWALT 20V

**IP RATING** 54

BUILT TO  
RESCUE



14





## ISO 9001-2015

The International for Standardization (ISO) is a network of national standards instituted in 157 countries. Each ISO member is the leading standards organization in its country. These members devise new standards, work to advance them, and team up with the ISO Central Secretariat to guide the technical groups that develop them.

They award certification only after registered, independent auditors review a company's process against strict ISO standards, and verify that the company has met established requirements, in both policy and practice.

TNT Rescue Systems Inc. is certified as an ISO 9001:2015 registered firm. This means you can be sure that TNT Rescue Systems Inc. products are designed and manufactured to the high standards our industry - and the ISO - demands. Certification covers all that we do to enhance customer satisfaction by meeting both customer and regulatory requirements, while continually improving performance.



PERFORMANCE,  
QUALITY  
AND SERVICE  
GUARANTEED!



# 15



# ONE KEY™

CUSTOMIZE. TRACK. MANAGE.

Item ID	Description	Status	Location	User	Timestamp
48-11-1880	M18™ REDLITHIUM HIGH OUTPUT™ X...	Demo Items (TNT)	Fire & Safety Shop		
48-59-1802	M18™ Dual Bay Simultaneous Rapid Cha...	Demo Items (TNT)	Fire & Safety Shop		
ATT-6.5	TNT Pump ATT 6.5	Loaner Items (TNT)			
BT-1.5	Bantam Pump 1.5	Loaner Items (TNT)	Fire & Safety Shop		
EBFC-320-18V	Storm Surge 320 Cutter F6	Demo Items (TNT)	Fire & Safety Shop	Brennen Lawson	
EBFCC-28-18V	Storm Surge Combi 28 M18V (F5)	Demo Items (TNT)	Fire & Safety Shop	Dennis Graybill	04/06/2024 2:06 PM

*FREE Inventory  
Management & Tracking  
System*



16







# ONE KEY™

CUSTOMIZE. TRACK. MANAGE.

The screenshot displays the Milwaukee ONE KEY web interface. At the top, the 'Inventory' section is active. The main content area shows details for a tool: 'EBFCC-28-18V Storm Surge Combi 28 M18V (F5)'. It includes a photo of the tool, a status of 'Available', and a 'Service' section with a date of '12/1/24'. A 'Tool history' table is visible below, showing two entries from 04/03/2024 and 03/31/2024, both at 'Fire & Safety Shop' with a status of 'Available' and 'Total Days' of 3. A map on the right shows the location of 'Fire & Safety Equipment Company' at 7854 Stage Rd, Concord, VA 24538, USA.

Date	Time	Place	Status	Total Days
04/03/2024	4:23 pm	Fire & Safety Shop	Available	3
03/31/2024	3:34 pm		Available	3



Set up on delivery!

17



**FIRE & SAFETY**  
EQUIPMENT COMPANY

FOR MORE DETAILED INFORMATION OR TO  
SCHEDULE A DEMO PLEASE REACH OUT:

**WWW.FIREANDSAFETY.COM**



**TNT@FIREANDSAFETY.COM**

